

Operation instruction

CoverLawn® CL 2802
Sport, Football, Rugby, Soccer

Operation and Renovation

Operation after complete integration:

The basic rule is that you operate the pitch according to the normal routines you have.

1. **Mowing** according to the normal routines.
2. **Aerating.** CoverLawn® (CL) back side distributes the pressure from the players leading to a reduction of compaction than a pitch without CL. Aerate the surface when needed. Use solid pipes (5-10 mm) when you aerate. If you use CL on a limited area manual aerating works fine.
 1. If you verticut or hollow pipes you risk the back side in CL or the machine itself. If the back side should be teared apart nothing happend ti the playing surface but the hybrid wil float around in the soil and in the long run your protection decreases.
3. **Growth.** If you have low growth the natural grass will disappear when the players wear it off. It doesn't affect CL but the playing surface will be a lot quicker and you will get different speed on the pitch. Playing on CL is like playing on very speedy artificial turf but on natural soil.
4. **Organic material** added like, grass, soil or sand jepordise the reinforcement since you add material on top of CL. Otherwise you will get a ned root zone on top of CL. Do not topdress unless CL is loose from the ground.

Renovation

1 time per year.

1. Brush/rake off old grass and other loose organic material. The piles should be visible
So you can see them on the surface. See picture right.
2. Remove the loose particles from the surface.
3. Return to normal renovation routines. Aerate with solid pipes.
4. Ensure good growth direct after renovation.
5. Return to normal pitch operation.

